

-1-

## PLACING FEATHERS ON A SURFACE

### BACKGROUND OF THE INVENTION

The present invention relates to computer generated graphics, in particular, the modeling and  
5 rendering of feathers using a computer.

Computer graphics are used in many different applications including computer games, movies and web pages. Graphically modeling and rendering of feathers for a realistic simulation of  
10 birds and other feather objects is a difficult task. In general, graphical feathers are generated on an ad hoc basis that consumes a significant amount of an artist's time to study and draw feathers. Thus, a systematic method for rendering feathers is useful.

### SUMMARY OF THE INVENTION

The present invention provides a computer implemented method for placing feathers on a surface. The method includes providing a surface having a plurality of vertices and establishing a growing  
20 direction for each of the plurality of vertices on the surface. Feathers are placed on the surface based on the plurality of vertices and the growing direction. In further embodiments, the feathers can be placed using a recursion or interpolation  
25 algorithm.

Another aspect of the present invention is a method for placing feathers on a surface including providing a surface having a plurality of vertices. Each vertex has a growing direction. The method also

includes performing a recursive algorithm to place a feather at each vertex. The algorithm includes finding a growing direction for vertices in the growing direction of the vertex. If the feather at  
5 the vertex collides with another feather, then the growing direction of the vertex is adjusted until there is no collision.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a general computing  
10 environment.

FIG. 2 illustrates an exemplary feather.

FIG. 3 illustrates a block diagram of an exemplary framework for a system.

FIG. 4 illustrates an exemplary user  
15 interface for modeling and rendering of individual feathers.

FIG. 5 illustrates example feathers rendered using the system illustrated in FIG. 3.

FIG. 6 is a schematic model of a feather  
20 for sampling a feather texture.

FIG. 7 illustrates rendering a feather according to an embodiment of the present invention.

FIG. 8 illustrates an exemplary framework for placing feathers on a surface.

25 FIG. 9 illustrates placing feathers on a wing and a tail skeleton.

FIGS. 10A-10D illustrate placing feathers on a polygon of a surface.

FIG. 11 illustrates a first bird and a  
30 second bird.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Prior to discussing the present invention in greater detail, an embodiment of an illustrative environment in which the present invention can be used will be discussed. FIG. 1 illustrates an example of a suitable computing system environment 100 on which the invention may be implemented. The computing system environment 100 is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the invention. Neither should the computing environment 100 be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment 100.

The invention is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well known computing systems, environments, and/or configurations that may be suitable for use with the invention include, but are not limited to, personal computers, server computers, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

The invention may be described in the general context of computer-executable instructions,

such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or  
5 implement particular abstract data types. The invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing  
10 environment, program modules may be located in both local and remote computer storage media including memory storage devices.

With reference to FIG. 1, an exemplary system for implementing the invention includes a  
15 general purpose computing device in the form of a computer 110. Components of computer 110 may include, but are not limited to, a processing unit 120, a system memory 130, and a system bus 121 that couples various system components including the  
20 system memory to the processing unit 120. The system bus 121 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and  
25 not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus  
30 also known as Mezzanine bus.

Computer 110 typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer 110 and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media includes both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer 110. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes

wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer readable media.

The system memory 130 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) 131 and random access memory (RAM) 132. A basic input/output system 133 (BIOS), containing the basic routines that help to transfer information between elements within computer 110, such as during start-up, is typically stored in ROM 131. RAM 132 typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit 120. By way of example, and not limitation, FIG. 1 illustrates operating system 134, application programs 135, other program modules 136, and program data 137.

The computer 110 may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 1 illustrates a hard disk drive 141 that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive 151 that reads from or writes to a removable, nonvolatile magnetic disk 152, and an optical disk drive 155 that reads from or writes to a removable, nonvolatile optical disk 156 such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage

media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The hard disk drive 141 is typically connected to the system bus 121 through a non-removable memory interface such as interface 140, and magnetic disk drive 151 and optical disk drive 155 are typically connected to the system bus 121 by a removable memory interface, such as interface 150.

The drives and their associated computer storage media discussed above and illustrated in FIG. 1, provide storage of computer readable instructions, data structures, program modules and other data for the computer 110. In FIG. 1, for example, hard disk drive 141 is illustrated as storing operating system 144, application programs 145, other program modules 146, and program data 147. Note that these components can either be the same as or different from operating system 134, application programs 135, other program modules 136, and program data 137. Operating system 144, application programs 145, other program modules 146, and program data 147 are given different numbers here to illustrate that, at a minimum, they are different copies.

A user may enter commands and information into the computer 110 through input devices such as a keyboard 162, a microphone 163, and a pointing device 161, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick,

game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 120 through a user input interface 160 that is coupled to the system bus, but  
5 may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A monitor 191 or other type of display device is also connected to the system bus 121 via an interface, such as a video  
10 interface 190. In addition to the monitor, computers may also include other peripheral output devices such as speakers 197 and printer 196, which may be connected through an output peripheral interface 195.

The computer 110 may operate in a networked  
15 environment using logical connections to one or more remote computers, such as a remote computer 180. The remote computer 180 may be a personal computer, a hand-held device, a server, a router, a network PC, a peer device or other common network node, and  
20 typically includes many or all of the elements described above relative to the computer 110. The logical connections depicted in FIG. 1 include a local area network (LAN) 171 and a wide area network (WAN) 173, but may also include other networks. Such  
25 networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer 110 is connected to the LAN 171 through  
30 a network interface or adapter 170. When used in a



WAN networking environment, the computer 110 typically includes a modem 172 or other means for establishing communications over the WAN 173, such as the Internet. The modem 172, which may be internal  
5 or external, may be connected to the system bus 121 via the user-input interface 160, or other appropriate mechanism. In a networked environment, program modules depicted relative to the computer 110, or portions thereof, may be stored in the remote  
10 memory storage device. By way of example, and not limitation, FIG. 1 illustrates remote application programs 185 as residing on remote computer 180. It will be appreciated that the network connections shown are exemplary and other means of establishing a  
15 communications link between the computers may be used.

In order to gain a better understanding of the present invention, an exemplary feather is illustrated in FIG. 2. Feather 200 is defined by a  
20 left outline curve 202 and a right outline curve 204. Additionally, feather 200 includes a rachis 206 and a plurality of barbs 208, for example a left barb 210 and a right barb 212. The geometry of feather 200 is defined by its rachis and the barbs distributed along  
25 both sides of the rachis. Vanes on both sides of rachis 206 carry the plurality of barbs. Each barb includes a series of barbules, which are projections off of the barbs.

FIG. 3 illustrates a block diagram of an  
30 exemplary framework for a system 250 in accordance

with an embodiment of the present invention. In system 250, several inputs are provided by a user in order for system 250 to model feathers. In order to model individual feathers, geometry input 252 and texture image input 254 are provided to system 250. Input 252 includes various parameters defining a geometric shape of the feather. The parameters of input 252 include outline curves 256, rachis curve 258, barb curves 260 and random seed 262. Texture image input 254 is used to define the texture and color of the feather. Inputs 252 and 254 are provided to an interface 264. Interface 264 provides an interactive interface for a user to selectively alter inputs 252 and 254. Additionally, interface 264 provides inputs 252 and 254 to a feather rendering system 266. To render individual feathers, system 266 includes a bi-directional texture function (BTF) module 268 and a parametric L-system module 270. The L-system module 270 is coupled to BTF module 268 in order to output and render synthetic feathers.

FIG. 4 illustrates an exemplary user interface 264 for modeling and rendering of individual feathers. The interface includes a rachis window 302 that defines the rachis curve of the feather. A barb window 304 illustrates barb curves with views from a perspective parallel with the rachis curve and perpendicular with the rachis curve. Window 306 is a sample feather texture image that has been input by a user. For example, a user may scan in or otherwise provide a sample feather that is to be

modeled and rendered by system 266. Additionally,  
window 308 illustrates outline curves of the feather.  
Each of the rachis curve in window 302, the barb  
curves in window 304 and outline curves in window 308  
5 may be interactively changed by a user in order to  
control the overall shape of the feather. Once these  
curves have been defined, system 266 is able to  
render individual feathers.

System 266 uses L-system module 270 to  
10 produce a base structure for the feathers. A feather  
can be regarded as a branching structure composed of  
repeated units called modules. An L-system represents  
the development of a branching structure by  
productions. A production replaces a predecessor  
15 module by several successor modules. A production can  
either be context-free and depend only on the module  
replaced, or be context-sensitive, in which case the  
production depends on the replaced modules as well as  
its immediate neighbor modules. Context-free  
20 productions can be of the form:

id: pred: cond  $\rightarrow$  succ

where id is the production label, and  
whereas pred, cond and succ are the predecessor,  
condition, and successor, respectively. The  
25 production is carried out only if the condition is  
met.

Given the rachis, barb, and outline curves  
as entered using interface 264, feather geometry can  
be modeled using a parametric L-system as follows:

$$\begin{aligned}\omega &: R(0) \\ p_1 &: R(i) : i < N \rightarrow [B_L(i,0)] [B_R(i,0)]R(i+1) \\ p_2 &: B_L(i,j) : j < M_L \rightarrow B_L(i, j + 1) \\ p_3 &: B_R(i,j) : j < M_R \rightarrow B_R(i, j + 1)\end{aligned}$$

5 (1)

where N defines the length of the feather as well as the density of the barbs at each side of the rachis while  $M_L$  and  $M_R$  define the lengths of the left and right barbs respectively. The axiom  $R(0)$  generates a feather based on the rachis and barb curves. Production  $p_1$  produces a small segment of the rachis according to the rachis curve and grows a barb on each side of the rachis using recursion. Production  $p_2$  creates a small segment of the left barb according to the left barb curve while production  $p_3$  proceeds similarly on the right barb with a right barb curve. Feather 340 in FIG. 5 shows a feather created using the above equation.

20 However, equation (1) above ignores the interaction between neighboring barbs and thus feathers appear unnatural. A feather geometry generated by equation (1) looks plausible but too regular. For a real feather, two lateral sets of barbs within the vane of the feather interlock the feather together. The interlocking is important for flight, keeping the air from rushing right through the feather. When the interlocking system of a feather is disturbed, as when a twig brushes through

a feather, random gaps form between the barbs on the same side of the rachis.

Neighboring barbs cling to each other by little hooks called cilium on the ends of the barbules if the total external force exceeds the holding capabilities of the cilium. To simulate this effect, external forces are introduced into our parametric L-system based on random seed parameter 262 as follows:

$$\begin{aligned}
 & \omega : R(0, 0, 0) \\
 & p_1 : R(i, F_L, F_R) : i < N \ \&\& \ F_L < F_0 \ \&\& \ F_R \leq F_0 \rightarrow [B_L(i, 0)] \\
 & \quad [B_R(i, 0)] R(i+1, F_L + F_e, F_R + F_e) \\
 & p_2 : R(i, F_L, F_R) : i < N \ \&\& \ F_L > F_0 \ \&\& \ F_R \leq F_0 \rightarrow \\
 & \quad [O_L B_L(i, 0)] [B_R(i, 0)] R(i+1, 0, F_R + F_e) \\
 & p_3 : R(i, F_L, F_R) : i < N \ \&\& \ F_L \leq F_0 \ \&\& \ F_R > F_0 \rightarrow [B_L(i, 0)] \\
 & \quad [O_R B_R(i, 0)] R(i+1, F_L + F_e, 0) \\
 & p_4 : R(i, F_L, F_R) : i < N \ \&\& \ F_L > F_0 \ \&\& \ F_R > F_0 \rightarrow \\
 & \quad [O_L B_L(i, 0)] [O_R B_R(i, 0)] R(i+1, 0, 0) \\
 & p_5 : B_L(i, j) : j < M_L \rightarrow B_L(i, j+1) \\
 & p_6 : B_R(i, j) : j < M_R \rightarrow B_R(i, j+1)
 \end{aligned}
 \tag{2}$$

where  $F_L$  and  $F_R$  are the total external forces on the left and right barbs respectively.  $O_L$  and  $O_R$  are directional rotations of the left and right barbs in response to  $F_L$  and  $F_R$ . The productions  $p_1$  and  $p_4$  produce a portion of the feather that, for each step along the rachis curve,  $F_L$  and  $F_R$  exceeds a threshold force  $F_0$  exerted by the cilium, the left (right) barb is rotated by a random angle  $\theta$  in a

direction determined by  $F_L$  ( $F_R$ ). The rotation of the barb is assumed to be within the tangent plane defined by the tangent vectors of the rachis and barb at the point where the rachis and barb intersect. The  
5 random rotation angle is computed as  $\theta = \lambda r_k(s)$  where  $r_k(s)$  is the k-th random number generated with random seed and can be a user-defined constant. After the rotation  $F_L(F_R)$  starts to accumulate again from zero. The random seed of each feather can be saved so that  
10 its shape remains the same every time it is rendered. FIG. 5 contains a number of feathers 341-344 created with random gaps between the barbs. The different feathers 341-344 are rendered by changing various feathers geometry parameters.

15 Equation (2) provides a feather structure including random gaps. Adding texture and color to the structure provides realistic rendering of the feathers. In order to provide texture to the feature structure, BTF module 268 captures the mesostructure  
20 and the directional radiance distribution at each point on the feather surface. A BTF is a 6D function  $T(x, y, \theta_v, \phi_v, \theta_l, \phi_l)$ , where  $(\theta_v, \phi_v)$  is the viewing direction  $v$  and  $(\theta_l, \phi_l)$  is the lighting direction  $l$  at surface point  $(x,y)$ . The BTF defines variation in  
25 pixel intensity based on a number of parameters.

To calculate the BTF, a geometry model is built for the barbs and barbules as shown in FIG. 6 according to the structure of the barbs and barbules. FIG. 6 illustrates a schematic model 360 of three

barbs 362 and a plurality of barbules 364 projecting from the barbs 362. This structure is rendered for all viewing and lighting settings. In one embodiment, the rendering is done offline so that a complicated  
5 geometry and sophisticated lighting models can be used. This model is opaque with both diffuse and specular reflections.

A sample line 366 of the BTF can be taken along an axis perpendicular to the barbs 362 to  
10 obtain a 5D BTF  $T_{bb}(x, \theta_v, \phi_v, \theta_l, \phi_l)$  for some constant  $y_0$ . A 5D BTF suffices for rendering the actual 6D BTF of a feather because of the spatial arrangement of barbs and barbules. The mesostructure of barbs and barbules is rendered such that fine-  
15 scale shadows, occlusions, and specularities are well-captured in the BTF  $T_{bb}$ . The rendering can be done offline by using a ray-tracer.

The above model of feather mesostructure has a number of advantages. First, the off-line BTF  
20 calculations allow capturing of a complicated mesostructure and directional radiance distribution at each surface point. Second, the BTF can model additional effects such as oil-film interference and iridescence, which is important for a class of  
25 familiar birds such as hummingbirds and ducks. Finally, a level-of-detail rendering can easily be supported with a BTF. As a result, the feather mesostructure can easily be simulated.

When rendering a feather, parametric L-  
30 system module 270 generates the feather at run-time.

By generating the feather at run-time, the storage requirement is modest for each feather because only its L-system parameters and the random seeds are stored; details such as barb curves (polylines) and the random gaps on the vane (the feather blade) are generated at run-time. After the feather structure is rendered using L-system module 270, BTF module 268 is used to efficiently draw the barb-barbule mesostructure on the feather structure and thus achieve realistic rendering for a wide range of viewing distances.

FIG. 7 illustrates the rendering of a feather. The feather L-system describes a barb 400 by a polyline 402 with vertices  $\{x_1, x_2, \dots, x_n\}$ . After polyline 402 is generated, texture is added by BTF module 268 to simulate the barb-barbule mesostructure. In one embodiment, a quadrilateral strip 404 including a plurality of polygons 406 is placed along the polyline 402 and the texture is added to each of the polygons 406. The local lighting direction  $l$  and viewing direction  $v$  are calculated at every vertex  $x_i$  of polyline 402 using the local coordinate frame at  $x_i$ . At each segment edge across the barb polyline 402, a 1D texture is created by looking up color values from BTF module 268 generated using the feather texture image in window 306 using the directions  $v(x_i)$  and  $l(x_i)$ . Thus,  $(n+1)$  1D textures are obtained. These textures are combined with the texture of the feather in each of the polygons 406 to render the barb 400 by multi-



texturing (application of several textures on the same object) and alpha-blending (altering of the transparency of an object), as is known in the art. When sampling the BTF with a ray tracer, parameters  
5 can be adjusted so that the BTF gives a "hard" or "soft" appearance to the feather. Furthermore, occlusions and specularities can be rendered as caused by the barb mesostructure.

Once individual feathers have been  
10 rendered, the feathers can be placed on a surface. FIG. 8 illustrates a framework 500 for placing feathers on a surface such as a bird. In framework 500, several inputs are provided to a bird rendering system 502 in order to output a model bird having  
15 feathers. The inputs include wings and tail skeletons 504, key feather positions and growing directions 506, a model of a surface or bird 508 and feather geometry 510. Using wings and tail skeletons 504, a user will place key feathers and orient growing  
20 directions of the feathers on the wings and tail skeletons. As described below, the wings and tail skeletons 504 and the key feather positions and growing directions on the wings and tail skeletons are provided to an interpolation module 512 within  
25 bird rendering system 502.

In order to place contour feathers, key feather positions and growing directions are provided on the model of a surface or bird 508. Inputs 506, 508, as well as the feather geometry 510 are provided  
30 to a recursion module 514. As discussed below,

recursion module 514 automatically places feathers onto a surface given the feather geometry 510 in order to detect and correct collisions between adjacent feathers.

5           Feathers are placed on the wings and the tail using skeletons 504 and key feather positions and growing directions 506. The feathers on a wing include the primaries, secondaries, humerals, primary coverts, and secondary coverts (these feathers are  
10 rooted on the scapula, ulna/radius, metacarpus and phalanx respectively). As shown in FIG. 9, a polyline 530 of line segments is used to represent the wing skeleton. Similarly a quadrilateral 532 is used as the skeleton for the tail. A bird has about 9 to 11  
15 primaries, 6 to 24 secondaries, and 8 to 24 tail feathers. The user can specify the numbers of feathers of each type and edit key feathers on the wing and key feathers on the tail using polyline 530 and quadrilateral 532. Interpolation module 512,  
20 using polyline 530 and quadrilateral 532, generates other feathers by interpolation.

FIG. 9 further illustrates placement of feathers on a wing. A model 534 includes a polyline 536, a surface model 538 and a plurality of segments  
25 540 indicating where on polyline 536 feathers are to be placed. Model 542 illustrates the placement of the feathers on the polyline 536 and model 544 illustrates small wing features placed on surface model 538.

Contour feathers are the feathers that cover the body of a bird. Given a polygonal model 508 describing a bird's body (without feathers), feathers of different sizes and shapes are placed on the model. The large number of feathers on a bird makes it difficult to manually place and edit individual feathers. A user can specify a number of key feathers and their growing directions using input 506 and system 502 the system automatically generates a full coverage of the bird based on the key feathers using recursion module 514. This full coverage is performed by recursion module 514 in three steps:

- a) re-tile the polygonal model 508 to generate feather growing positions,
- 15      b) interpolate the key feather growing directions to all feather growing points to get an initial growing direction at each point, and
- 20      c) recursively determine the final feather growing direction at every feather growing point, with collisions between feathers detected and rectified.

The output of recursion module 514 is a feather placement map indicating feather growing positions and directions. The feather shape parameters (i.e. outline curves 256, rachis curve 258 and barb curves 260) can be estimated from that of nearby key feathers or provided with model feather input 510. These shape parameters are used to generate a simplified geometry for each feather. This

simplified geometry is used for collision detection in step (c) above.

The vertices of the given polygonal model 508 are difficult to use as feather growing positions. Feathers at different parts of a bird have different sizes, for example small feathers need to grow densely in order to cover the bird's skin. In addition, feathers tend to distribute evenly in a region of constant feather density. Vertices of a 10 conventional polygonal model often do not have evenly distributed vertices or account for increased feather density in positions where the feathers are small. To address this problem the polygonal model 508 can be retiled using a suitable re-tiling algorithm as is 15 known in the art. This re-tiling creates a polygonal model whose vertices are evenly distributed over a region of constant density.

A simple technique may also be used for adjusting vertex density based on curvature. This 20 technique can be used to control vertex density based on the sizes of feathers. In one embodiment, the sizes from the key feathers are estimated using Gaussian radial basis functions, where a radius is defined as a distance over a surface, as computed 25 using a shortest path algorithm. The user has control over the spatial extent and weight of each basis function. This estimation scheme is used for creating vector fields on a polygonal surface. Ultimately, vector fields for vertices are created for the 30 polygonal model. After re-tiling, the vertices of the

new polygonal model are the feather growing positions.

From the growing directions of key feathers, initial growing directions are calculated  
5 at all vertices using Gaussian radial basis functions as described above. The initial growing directions tend to cause inter-penetration of feathers because these directions are derived without any consideration to the shapes of the feathers. To  
10 determine the final growing directions, collision detection is performed on the feathers based on a simplified geometry and the feather growing directions are adjusted accordingly. Because of the large number of feathers and the complex shape of a  
15 bird's body, a collision detection between every pair of feathers is likely to be very expensive. To address this problem two strategies are adopted. First, feathers are grown in an orderly fashion according to the initial growing directions. Second,  
20 local collisions between neighboring feathers are only considered because collisions rarely happen between feathers far away from each other (two feathers are neighboring feathers if their growing positions are connected by an edge of a polygon). A  
25 recursive collision detection algorithm is used in recursion module 514 to implement these strategies.

As FIGS. 10A-10D illustrate, vertices around each vertex  $v$  are classified into two groups according to the initial growing direction  $o_v$  for  $v$ .  
30 The first group includes vertices in the growing

direction and the second group includes vertices not in the growing direction.

After the vertices around every vertex are classified, recursion module 514 invokes the following recursive collision detection algorithm at each vertex.

```
FindGrowingDirection(v)
{
    If the growing direction at v has already
10     been found, return;
    For each vertex v' in the growing direction
        v, FindGrowingDirection(v');
    While feather(v) collides with feather(v')
        for some vertex in the growing
15     direction, adjust the growing
        direction at v;
    For each vertex v' not in the growing
        direction, FindGrowingDirection(v');
}
```

20 Here feather(v) and feather(v') are the feathers at vertices v and v', respectively. A vertex v on the re-tiled model 508 with initial growing direction  $o_v$  is shown in FIG. 10A. The vertices around v are vertices  $v_0$  through  $v_5$ . Among these,  $v_1$  and  $v_2$  are in the growing direction, whereas  $v_3$ ,  $v_4$  and  $v_5$  are not in the growing direction. According to the algorithm above, the final growing directions at  $v_1$  and  $v_2$  is first determined by recursion as illustrated at FIG. 10B. Based on the final growing directions at

30  $v_1$  and  $v_2$  as well as the shapes of feathers at v,  $v_1$

and  $v_2$ , collision between the feathers can be detected and the feather growing direction at  $v$  can be adjusted by rotating feather  $v$  toward the surface normal at  $v$  as shown at FIG. 10C. Rotation can be performed in small increments, so that rotation can stop as soon as there are no collisions detected. The growing direction at  $v$  is then final and the growing directions for  $v_0$ ,  $v_3$ ,  $v_4$  and  $v_5$  can be processed through using the recursion algorithm above as shown at FIG. 10D. For faster collision detection, a simplified geometry can be used for each feather.

FIG. 11 illustrates a sample bird 550 having feathers placed according to initial growing directions and a sample bird 552 having feathers rendered according to the algorithm above. In sample bird 550, there are numerous inter-penetrating feathers and many feathers that grow inside the bird's skin as illustrated at 551. When using the recursion algorithm above with recursion module 514, sample bird 552 having a realistic rendering is achieved.

Although the present invention has been described with reference to particular embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.